

7A7



7A7

REMOTE-CUTOFF PENTODE

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathode:

Voltage. 6.3[□] ac or dc volts
 Current. 0.3^{□□} amp


Direct Interelectrode Capacitances:[○]

Grid No.1 to Plate . . . 0.005 max. μ f
 Input. 5.5 μ f
 Output 7.0 μ f

[○] With no external shield.**Mechanical:**

Mounting Position. Any
 Maximum Overall Length 2-25/32"
 Maximum Seated Length 2-1/4"
 Maximum Diameter 1-3/16"
 Bulb T-9
 Base Lock-in 8-Pin
 Basing Designation for BOTTOM VIEW 8V

Pin 1 - Heater
 Pin 2 - Plate
 Pin 3 - Grid No.2
 Pin 4 - Grid No.3
 Pin 5 - Internal
 Shield



Pin 6 - Grid No.1
 Pin 7 - Cathode
 Pin 8 - Heater
 Plug - Base
 Shell

Maximum Ratings, Characteristics, and Typical Operating Conditions are the same as those for Type 6SK7

- Nominal voltage = 7.0 volts.
 □□ Nominal current = 0.32 ampere.

JUNE 20, 1947

TUBE DEPARTMENT
 RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA